

STARK ENGINEERING & HARDWARE PTY. LTD.

A.B.N. 28 612 383 716

A.C.N. 010 080 350

96 LAIDLEY ROAD, FOREST HILL, QLD. 4342

Ph (07) 5465 4195

A/H (07) 5465 4368

Fax (07) 5465 4190

Mobile 0428 889 148

E-mail: sales@starkeng.com.au

Web site: <http://www.starkeng.com.au>

Incorporating the business of



HYDRAULIC HALAL RESTRAINT BOX MARK IV OIE APPROVED

Features:

- Access full opening walk in
- Hydraulic controls mounted on pivot arm
- Body & head restraints and “rollover” operated with individual single cylinder hydraulic rams
- Rubber cushion support
- Full side gate for easy access
- Heavy duty construction duralgal material
- Hot dipped galvanised (Optional)
- Full checker plate floor
- Grease nipples fitted to moving joints where necessary
- Single phase 2.2kw electric motor
- Oil capacity 45 litre holding tank
- Hydraulic pump immersed in oil & direct coupled to motor
- 9.4 litre per minute pump @ 1400rpm
- Manufactured weight is 1000kg

Restraint Box MKIV has been approved to the standard of the World Organisation for Animal health (OIE) Code, with the approval of the Australian Chief Veterinary Officer (ACVO).



STARK ENGINEERING & HARDWARE PTY. LTD.

A.B.N. 28 612 383 716

A.C.N. 010 080 350

96 LAIDLEY ROAD, FOREST HILL, QLD. 4342

Ph (07) 5465 4195 A/H (07) 5465 4368
Fax (07) 5465 4190 Mobile 0428 889 148

E-mail: sales@starkeng.com.au

Web site: <http://www.starkeng.com.au>

Incorporating the business of



RESTRAINT BOX

Mark IV Restraint Box OIE Approved

The Australian Chief Veterinary Officer (ACVO) assessment found that proper use of the Mark IV Restraint Box is consistent with the requirements of the World Organisation for Animal Health (OIE) Code, on this basis slaughter of cattle using the Mark IV Restraint Box was found to have ongoing appropriateness.



The Hydraulic Restraint Box comes in three power unit variations, A. Manual Hand Pump; B. 240V .75kw Electric; C. 240V 2.2kw Electric. Some minor aspects of the illustrations below vary dependent on model.

